

ASTROLITE HIGH

S3 SRC 0% METAL 37 - 47



SIZE	Reference
37	9ASTH37
38	9ASTH38
39	9ASTH39
40	9ASTH40
41	9ASTH41
42	9ASTH42
43	9ASTH43
44	9ASTH44
45	9ASTH45
46	9ASTH46
47	9ASTH47

General Descriptions / Fabrics

Upper	Full grain leather
Lining	Breathable mesh
Toecap	Composite
Midsole	Textile Wellmax®
Outsole	Single density PU

Packaging



10 pairs in 1 carton

Specific Advantages

- ✚ Sole slip resistant on ceramic and steel
- ✚ Energy absorption by the heel
- ✚ Sole antistatic
- ✚ Closed backpoint
- ✚ Composite material
- ✚ Light and flexible

General Norms Standard Explanation

EN 20345: This standard specifies basic and additional (optional) requirements for safety footwear used for general purpose. It includes, for example, mechanical risks, slip resistance, thermal risks, ergonomic behaviour.

This footwear includes the necessary safety device to protect the wearer's toes against risk of injury from falling objects and accidents which could occur in industrial environments. Fit out with a toe cap, this footwear protects the wearer's toes against crushing impacts with a protection provided on 200 Joules.

Standards

This shoe is in conformity with the model of the individual safety equipment which corresponds to

The EC Type-Examination certificate LEC FI00340789

Delivered by **INTERTEK (notified body n° 0362)**

EN ISO 20345:2011

CLASSE S3 SRC



S3

SRC

Protections afforded by the standard:

- Protective shell 200 J
- Closed backpoint
- Antistatic
- Energy absorption by the heel
- Water penetration and absorption
- Anti-perforation sole
- Anti-slip sole
- Sliding resistant